

Rugged[®] RAID PRO MOBILE RAID DRIVE Data Sheet

Compact. Field-Proven. Versatile.

- Integrated SD card reader
- Hardware RAID 0/1 flexibility for speed or redundancy
- New USB-C connector for next-generation computers
- Included USB 3.0 adapter works with PC or Mac[®]
- Shock, dust, and water resistance for all-terrain use

design by neil poulton

Field-Proven Durability With Greater Versatility.

The LaCie Rugged[®] RAID Pro marries signature on-the-go Rugged durability with RAID's adaptability. Thanks to the embedded SD card reader, it's now easier to back up content in the field. Configurable with the LaCie[®] RAID Manager, this drive is a reliable travel companion for busy videographers and professional photographers. Do you need to prioritize spacious capacity with speedy transfer rates? Are you concerned about the safety of your footage on the go? Either way, the Rugged RAID Pro is the ideal solution for you.

Tough, On-the-Go Storage for Any Terrain.



Creative pros rely on LaCie Rugged drives whenever they need to capture, transport, and transfer data in the field. With resistance to drops, crushes, rain, and shocks, even in extreme conditions, the Rugged RAID Pro goes the extra mile for you—so you can go places.

Extra Protection for Your Data.

- Drop resistance: 4-ft (1.2m)¹
- Crush resistance: 1-ton car²
- Dust/Water resistance: IP54 Protection against dust and rain
- 3-year limited warranty and Rescue Data Recovery Services plan

1 In nonoperating mode

2 Determined by a test that approximates a real-world scenario in which the hard drive remained functional, despite aesthetic damage, after the product was driven over by an approximately 1-ton car (1000kg/2205 lbs).

Rugged® RAID PRO

LACIE



MOBILE RAID DRIVE

Retail Packaging	Product Dimensions	Box Dimensions	Master Carton Dimensions	Pallet Dimensions	
Length (in/mm)	3.583in/91mm	3.465in/88mm	14.409in/366mm	47.992in/1219mm	
Width (in/mm)	1.181in/30mm	4.724in/120mm	7.598in/193mm	40in/1016mm	
Depth (in/mm)	5.512in/140mm	7.205in/183mm	10.433in/265mm	47.323in/1202mm	
Weight (lb/kg)	1.058lb/0.48kg	1.389lb/0.63kg	11.861lb/5.38kg	769.634lb/349.1kg	
Quantities					
Boxes per Master Carton	8				
Master Cartons per Pallet	60				
Pallet Layers	4				

- Computer with a USB-C, USB 3.0 or USB 2.0 port
- Latest version of Windows[®] 7 and later / Mac OS[®] X 10.9 and later
 Minimum free disk space: 600MB recommended
- Minimum free disk space: 600MB recommended
- LaCie Rugged[®] RAID Pro
- USB-C (USB 3.1 5Gb/s) cable
 - USB-C to USB-A cable
 - Removable cover and spare
 - Power supply (for use with USB 3.0 connection)
 Quick Install Guide

Region	Model Number	Capacity	Color	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
ww	STGW4000800	4TB	Orange	3	763649126646	3660619403745	10763649126643

LACIE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cuperlino, California 95014, United States, 408-658-1000 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2018 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, LaCie, and the LaCie logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. LaCie Rugged is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. DS1975.1-1803US